

Technical Specifications: UC^X50E

System Processor:

- Built-in Intel® Dual-core Atom™ D2800 (1.86GHz) Processor

Network:

- 2 On-Board Gigabit/100/1000T Ethernet

Hard Drive and Memory:

- SSD 80Gb Hard Drive
- 2GB RAM

Additional Interfaces:

- Trunk Expansion Slot (1)
- USB (for external back-up)
- Supported Trunk Cards:
 - T1/E1 PRI trunk card (1 or 2 span)
 - 4-port FXO trunk card
 - 8-port FXO trunk card
 - BRI trunk card

System Cooling

- Heat sink on CPU
- 40mm case fan

Power:

- External Adapter 120W 90V-240V AC to DC12V Power Adapter 2.5m plug.

Dimensions:

- 8"(L) x 8"(W) x 3.5" (H)

Shipping Parameters

- Dimensions: 12" X 12" X 12" (30x30x30cm)
- Weight: 6Lbs (2.7 Kg)

Maximum Number of Extensions:

- UC^X50E supports a maximum of 80 extensions (80 concurrent calls)

System Recording Capacity:

- 2,400 hours for Call Recording and Voicemail

Supported Telephony Devices:

- Supported Nortel telephones:
 - Nortel 1100, 1200 & 2000 series, i2050 softphone
 - Nortel T/M series digital telephones
 - Nortel M3900, M2000 series digital telephones
- Mobility – 4G, SIP Wifi
 - iPhone, Android, handheld/tablet
- Supported SIP telephones:
 - Yealink, Polycom, Cisco, Counterpath BRIA
- FXS/FXO, T1/E1 Gateways – Grandstream, Digium

GSM – E-MetroTel Gateway

